## BEST AVAILABLE COPY

#### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

7145573347

### **Listing of Claims:**

- 1-17. (Cancelled.)
- 18. (Currently Amended) A switch comprising:
- a plurality of ports including (i) a first plurality of ports adapted for couplinged to a plurality of devices, including a source device being a member of a first network and a destination device being a member of a second network, associated with at least two networks, and (ii) a second plurality of ports directly coupled to a router so that the switch is interposed between the router and the plurality of devices; and

a mechanism to determine, using layer three (L3) information contained in a packet received by a source port of the plurality of ports, which one of the plurality of ports is coupled to the destination device and to transfer information contained in the packet to the destination device without use of a routing function.

- 19. (Cancelled.)
- 20. (Original) The switch of claim 18, wherein the mechanism analyzes data transmitted between the router and the destination device.
- 21. (Original) The switch of claim 20, wherein the data is packetized in accordance with an Address Resolution Protocol.
- 22. (Previously Presented) The switch of claim 18, wherein the mechanism generates a data structure including layer two (L2) addresses and corresponding layer three (L3) addresses associated with the destination device prior to transferring information to the destination device.

- 23. (Currently Amended) The switch of claim 18, wherein the destination device includes a server associated with the first network of being a virtual local area network of one of the at least two virtual local area networks.
  - 24. (Currently Amended) A switch comprising:
- a plurality of ports adapted for coupling together a plurality of <u>virtual local area</u> networks being at least three <u>virtual local area</u> networks, at least one of the plurality of ports is directly coupled to a router; and

a mechanism to (a) analyze information transferred from a source device of a first <u>virtual local area</u> network to a destination device of a second <u>virtual local area</u> network, (b) store information identifying a port coupled to the second <u>virtual local area</u> network, a layer two (L2) address of the destination device and a layer three (L3) address of the destination device corresponding to the L2 address, and (c) using the information to forward data between the plurality of <u>virtual local area</u> networks.

- 25. (Original) The switch of claim 24, wherein the information is obtained from packets configured in accordance with an Address Resolution Protocol.
- 26. (Original) The switch of claim 24, wherein the mechanism uses the information by (i) determining both the L2 address of the destination device and the port coupled to the second network based on the L3 address of the destination device supplied by the source device, and (ii) setting a destination of packets of the data to the L2 address of the destination device.
  - 27. (Cancelled.)
  - 28. (Currently Amended) A network comprising:
  - a destination device of a first network;
  - a source device of a second network;
  - a router; and
- a switch having a plurality of ports supporting communications to the destination device and operating transparently to the destination device, the source device and the router, the source

Docket No: 082771.P118C

device and the router with one of the plurality of ports directly coupled to the router, the switch including software to determine, using layer three (L3) information contained in a packet received by a first port coupled to the source device, which one of the plurality of ports is coupled to the destination device, to produce a data structuretable including layer two (L2) addresses and corresponding layer three (L3) addresses associated with the destination device and to transfer information contained in the packet from the source device to the destination device without use of a routing function.

29. (Currently Amended) The network of claim 28, wherein the first network is separate and distinct from the second network and the switch is remotely located from the router.

30-36. (Cancelled.)

- 37. (Currently Amended) For use in transferring data from a first <u>virtual local area</u> network to a second <u>virtual local area</u> network via a switch directly coupled to a router and interposed between the router and the first and second <u>virtual local area</u> networks without assistance by the router, the method comprising:
- (a) receiving a data packet by the switch, the data packet originating from a source device associated with the first <u>virtual local area</u> network and including a layer three (L3) address of a destination device of the second <u>virtual local area</u> network;
- (b) determining the L2 address associated with the L3 address of the destination device through access of one or more data structures within the switch and a port of the switch to which the destination device associated with the L3 address is attached; and
  - (c) setting a destination address of the data packet to the L2 address,

wherein the operations (a), (b) and (c) are conducted transparent to the source device, the destination device and the router.

38-43. (Cancelled.)

44. (Currently Amended) The switch of claim 1718, wherein the source port is coupled to thea first network being a virtual local area network.

Docket No: 082771.P118C

Page 4 of 10

WWS/sm

(Currently Amended) The switch of claim [[44]]22, wherein the one of the 45. plurality of ports is coupled to a second network data structure is a table.

7145573347

- (Currently Amended) The switch of claim 45 operating transparent to the source 46. device, the destination device and the router, wherein the first network is a first virtual local area network.
- (Currently Amended) The switch of claim 4645, wherein the second network is a 47. second-virtual local area network is different from the first virtual local area network.
- (Currently Amended) The switch of claim 187, wherein a lack of usage of the 48. routing function is a lack of use of a routing protocol.
- (Previously Presented) The network of claim 28, wherein a lack of usage of the 49. routing function is a lack of use of a routing protocol.
- (Previously Presented) The method of claim 37, wherein the one or more data 50. structures is a table.
- (Previously Presented) The method of claim 37 further comprising sending the 51. data packet to the destination device.
  - 52. (Cancelled.)
- (Currently Amended) Directly coupled to a router and in communication with a 53. destination device, a The-switch of claim 52, wherein-comprising:

a plurality of portsthe plurality of ports includinges a first plurality of ports adapted for communication with a plurality of devices including the destination device, the first plurality of ports being associated with at least two virtual local area networks; and

a mechanism to utilize a data structure including layer two (L2) information and corresponding layer three (L3) information associated with the destination device, the data

Docket No: 082771.P118C

structure being accessed to determine which one of the plurality of ports is coupled to the destination device and to send information contained in the packet to the destination device with the L2 information in the packet unchanged in order to reduce traffic on the router.

7145573347

- 54. (Previously Presented) The switch of claim 53, wherein the plurality of ports further includes a second plurality of ports coupled to the router.
- 55. (Currently Amended) The switch of claim 5253, wherein the mechanism further analyzes data transmitted between the router and the destination device.
- 56. (Previously Presented) The switch of claim 55, wherein the data is packetized in accordance with an Address Resolution Protocol.
- 57. (Currently Amended) The switch of claim 52-53 being physically removed from the router.
- 58. (Currently Amended) The switch of claim 5253, wherein the data structure is a table.
  - 59. (Cancelled.)
- 60. (Currently Amended) A The switch of claim 59, wherein the comprising:

  an input comprises a plurality of ports including a first plurality of ports being adapted for communication with a plurality of devices including the a destination device and a second plurality of ports being adapted for direct coupling to a router so that the switch is interposed between the plurality of devices and the router, the first plurality of ports being associated with at least two three virtual local area networks; and

a mechanism to determine, using layer three (L3) information contained in a packet received over the input, how the destination device is coupled to the input and to transfer information contained in the packet to the destination device without use of a routing protocol.

Docket No: 082771.P118C

Page 6 of 10

WWS/sm

P.11/14

Appl, No. 09/488,945 Amdt. Dated 10/12/2004 Reply to Office Action of 9/8/2004

- (Currently Amended) The switch of claim 5960, wherein the mechanism 61. analyzes data transmitted between the router and the destination device.
- 62. (Previously Presented) The switch of claim 61, wherein the data is formatted in accordance with an Address Resolution Protocol.

7145573347

- (Currently Amended) The switch of claim 59-60 being physically removed from 63. the router and operating transparent to the router and the plurality of devices.
- (Currently Amended) Directly coupled to a router and in communication with a 64. destination device, a switch comprising:

a data-structure table configured to contain layer two (L2) addresses and corresponding layer three (L3) addresses associated with multiple destination devices; and

logic to populate the data structure table based on information received from the router during initial communications with the destination device and, for communications after the initial communications, to utilize the data-structuretable to obtain an L2 address for the destination device for forwarding incoming information to the destination device without accessing the router.

- (Previously Presented) The switch of claim 64, wherein the initial communication includes a query in accordance with an Address Resolution Protocol.
- (Previously Presented) The switch of claim 64, wherein the data structure is a 66. table.
- 67. (Currently Amended) Directly coupled and in communication with a router, a switch comprising:

a data structure to store a layer three (L3) address and a layer two (L2) address corresponding to the L3 address associated with a device located in a second local area network;

means for forwarding a packet if the L3 address of a destination device of the packet, located in a first virtual local area network, matches an L3 address in the data structure, wherein

Docket No: 082771.P118C

the switch does not process the packet if the L3 address of the destination device matches the L3 address in the data structure; and

means for communicating the packet to a router if the L3 address of the destination device does not match any L3 address in the data structure.

wherein the means for forwarding and the means for communicating operate transparent to the device, the destination device and the router and the switch is deployed to intercept the packet directed to the router.

- 68. (Currently Amended) The switch of claim 67, wherein the data structure is a table including L2 address and a corresponding L3 address for each destination device of <u>thea</u> first <u>virtual</u> local area network.
- 69. (Currently Amended) The switch of claim 68, wherein the packet is sent from thea device located in thea second virtual local area network different from the first virtual local area network.
  - 70. (Cancelled.)
  - 71. (Currently Amended) A method comprising:
- (a) storing a layer three (L3) address and a layer two (L2) address corresponding to the L3 address in a data structure table of accessible by a switch;
- (b) forwarding a packet to a destination device <u>placed on a first virtual local area network</u> with the packet being processed by the switch if an L3 address of the destination device of the packet matches an L3 address in the data structure; and
- (c) communicating the packet to a router directly coupled to the switch if the L3 address of the targeted destination device does not match any L3 address in the data structuretable, wherein the switch is implemented to intercept the packet directed to the router.
- 72. (Previously Presented) The method of claim 71, wherein the string of the L3 address and the corresponding L2 address is in a table contained in the switch.

WWS/sm

- 73. (Currently Amended) The method of claim 72, wherein prior to forwarding of the packet, the method further comprises receiving the packet from a source device by the switch, the source device being placed on a second virtual local area network.
- 74. (Previously Presented) The method of claim 73, wherein the source device and the destination device are placed in different virtual local area networks. and the operations (a). (b) and (c) are conducted transparent to the router and the destination device
- 75. (New) The method of claim 72, wherein the operations (a), (b) and (c) are conducted transparent to the router and the destination device.

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

# **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked	<b>i</b> : -
☐ BLACK BORDERS	, ·
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES	
☐ FADED TEXT OR DRAWING	
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING	
☐ SKEWED/SLANTED IMAGES	
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS	
☐ GRAY SCALE DOCUMENTS	
☐ LINES OR MARKS ON ORIGINAL DOCUMENT	
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY	
□ other:	

## IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.